



Features:

*** Material:**

1. Insulator: UL 94V-0 PBT
2. Contact: Copper alloy
3. Package Material: ESD TRAY & ESD TAPE

*** Color: Black**

*** Accept PCMCIA TYPE , I,II, III
Card Ordering Information**

Ordering Information:

1279	*	H	C	*	J0*
1	2	3	4	5	6

1. Series No.
2. A=Single stack
3. H = Through hole
4. C = With guide, without ejection bar
5. Contact plating
 F = Selective gold flash over 50u" nickel
 J = Selective 15u" gold over 50u" nickel
 X = Selective 10u" gold over 50u" nickel
6. TOP TYPE, Voltage spec.:

DIM B = 1.1mm	DIM B = 2.2mm
Voltage 5V	Voltage 3.3V
1279*HC*J00	1279*HC*J0V

screws are not included with

PIN TYPE	DIM. L	PIN NUMBER
DETECT	3.50	36,67
GENERAL	4.25	ALL OTHER PINS
POWER	5.00	1, 17, 34, 51, 68

**GENERAL TOLERANCES:
(UNLESS SPECIFIED)**

1 PLACE	± 0:3
2 PLACE	± 0:2
3 PLACE	± 0:1
4 PLACE	± --
ANGULAR ±1/2°	

Maßstab: 1:1		(Gewicht) x g	
Werkstoff: Halbzeug		Material	
Datum 15.08.14		Name	
Bear. 15.08.14		Norm	
Zust.		Änderung	
Datum		Nam.	
Urspr.		(Ers.f.:	
		(Ers.d.:	
		A3	

**PC CARD PLUG
1279AHC*J00**

Blatt
. Bl.